

PRACTICAL

ACCEPTANCE

SAMPLING

A HANDS-ON GUIDE

GALIT SHMUELI

UNIVERSITY OF MARYLAND

ISBN-13: 978-1-461-04130-6

ISBN-10: 1-461-04130-9

Copyright © 2011 by Galit Shmueli

ALL RIGHTS RESERVED. Printed in the United States of America. No part of this work may be used or reproduced, transmitted, stored or used in any form or by any means graphic, electronic, or mechanical, including but not limited to photocopying, recording, scanning, digitizing, taping, Web distribution, information networks or information storage and retrieval systems, or in any manner whatsoever without prior written permission.

For further information see www.galitshmueli.com

Table of Contents

Preface	1
Chapter 1: Introduction.....	3
1.1 Acceptance Sampling in Industry and Commerce	3
1.2 Who Should Understand Acceptance Sampling?	4
1.3 What Are Sampling Plans?	4
1.4 Terminology	5
1.5 What determines a sampling plan?	6
Producer's Side:	6
Consumer's Side:.....	6
1.6 Problems	7
Chapter 2: Single-Stage Plans for Attributes (Categorical Measurements).....	9
2.1 Computing Acceptance Probabilities	9
Example: Acceptance Sampling of Automobile Tires.....	10
Consumer's View: Per-Batch Computations	10
Producer's View: Manufacturing Process Computations	13
Equivalence of Producer and Consumer Computations in Large Batches	15
2.2 The Operating Characteristic (OC) Curve	15
Effect of n and c on Acceptance Probabilities and Risks.....	17
2.3 Designing a Sampling Plan	19
2.4 ANSI/ASQC Z1.4 (Military Standard 105-E) Tables.....	20
Design of Sampling Tables	20
Table Usage	20
Online Plans: SQCOnline.com	23
2.5 Single-Stage Plans for Multiple Defects-per-Unit	26
2.6 Sampling Plans for Specified Producer and Consumer Risks	27
2.7 Problems	28

Chapter 3: Double-Stage Plans for Attributes	31
3.1 Double-Stage Sampling Procedure	31
3.2 Why Use Double-Stage Plans?	31
3.3 Probability of Acceptance and OC Curves.....	32
Example: Automobile Tires	32
3.4 Expected Amount of Inspection.....	34
3.5 ANSI/ASQC Z1.4 Tables (Mil-Std105E)	35
Table Usage.....	35
Online Plans	36
3.6 Problems	37
Chapter 4: Rectifying Sampling Plans	39
4.1 Single-Stage Rectifying Plans	39
Choosing n and c	40
AOQL-Based Plans.....	40
LTPD-Based Plans	42
4.2 Double-Stage Rectifying Plans	43
4.3 Problems	46
Chapter 5: Inspection Plans for Variables (Continuous Measurements)	49
5.1 Example: Organic Milk Distribution	49
5.2 Specification Limits	49
5.3 Procedure.....	50
5.4 The Normality Assumption	51
What if normality is not a reasonable assumption?	51
5.5 Known vs. Unknown Process Standard Deviation	52
5.6 k -Method: Distance of Sample Mean from Specification Limit.....	53
Lower Specification Limit	53
Upper Specification Limit.....	55
5.7 M -Method: Limit on Proportion of Non-Conforming Items.....	55
Lower Specification Limit	55
Upper Specification Limit.....	57

	Double Specification Limit	57
5.8	ANSI/ASQC Z1.9 Tables (Military Standard 414).....	57
	Design of Tables	58
	Table Usage	58
	Online Plans.....	63
5.9	Sampling Plans for Given Producer and Consumer Risks	65
5.10	Problems	66
	Chapter 6: Continuous Sampling.....	69
6.1	Continuous Sampling Plan 1 (CSP-1).....	70
	Procedure.....	70
	Performance Measures and Choosing i and f	71
	Non-Rectifying CSP-1	74
6.2	Continuous Sampling Plan 2 (CSP-2).....	74
6.3	Mil-Std 1235 Tables.....	75
	CSP-1 and CSP-2	75
	Plan CSP-F for Short Production Runs.....	77
	Multi-level Plan CSP-T	78
	Plan CSP-V	78
6.4	Online Plans.....	79
6.5	Skip-Lot Sampling Plans	80
6.6	Problems	82
	Index.....	85

Chapter 1: Introduction

1.1 Acceptance Sampling in Industry and Commerce

In today's manufacturing world, the path from raw materials to final product often takes place over multiple companies and across multiple continents. A company selling laptop computers has likely sub-contracted different parts to different sub-contractors. The assembly might take place in yet another plant. And the packing and shipping, from yet another location. In order to assure a certain quality level, companies use inspection at the different supply chain stages.

Acceptance Sampling, also known as *Sampling Inspection*, consists of quality assurance schemes designed to test whether the quality of batches of products or services conform with requirements, based on inspecting *only a sample* from each batch. The use of sampling inspection relies on the premise that products need not conform 100% with specification requirements, and it is often more economical to allow a small percentage of non-conforming items to pass on for later rejection than to bear the expense of 100% inspection. Acceptance sampling provides criteria and decision rules for determining whether to accept or reject a batch based on a sample. Civilian ISO acceptance sampling plans and their military counterparts (Mil-Std) are commonly used standards in industry. These plans dictate the sample size to be drawn from each batch, and the requirements that the sample must meet to assure that the entire batch is of acceptable quality.

Acceptance sampling is useful for testing the quality of batches of items, especially when a large number of items must be processed in a short time. However, acceptance sampling is *not* a method for monitoring or improving the quality of a process. It is important to keep this in mind and to use other quality control tools such as control charts for monitoring and designed experiments for improvement.

The origin of Acceptance Sampling is in World War II, for testing the quality of bullets in the United States' military. The need for sampling arose from the destructible nature of bullet testing. In general, acceptance sampling is needed either when inspection is destructive, or when inspecting each item (*100% inspection*) is prohibitively expensive or time-consuming.

4 Introduction

Acceptance sampling is commonly used in contracting and sub-contracting, where the contractor wants to assure the quality of the incoming goods or services. For example, a school providing lunch services inspects the food quality on a daily basis. A large cosmetics company inspects the quality of the products in each shipment that it receives from its overseas manufacturers. A large mining manufacturing company in the USA uses acceptance sampling to inspect machined parts from its vendors. The famous coffee chain Starbucks uses acceptance sampling to assure the quality of coffee shipments from its different suppliers.

“Because of Starbucks’ high volume, coffee exporters competed to become suppliers. For its part, Starbucks cultivated long-term relationships with its suppliers, providing training working closely with them. For quality control, Starbucks extracted three different samples from every shipment: one before the export was arranged, one just before shipment and one on arrival at the roasting plant. At each stage Starbucks reserved the right to refuse the shipment.”

(from The Starbucks Brand case study, Rotman School of Management, University of Toronto, accessed Mar 14, 2011)

Acceptance sampling is also commonly used by manufacturers or suppliers themselves, as a tool for audit or compliance. A well-known vendor of child safety car seats inspects the quality of its products using acceptance sampling. A call center audits a sample of calls in each shift to assure quality service. A manufacturer and exporter of home textiles in India employs inspection after the fabric cutting stage, after sewing, and after packing. Manufacturers of electronic parts in China use sampling inspection to assure that shipments of their parts will be up to the standard of their purchasing companies.

1.2 Who Should Understand Acceptance Sampling?

Everyone who is involved in the inspection phase should be literate of what acceptance sampling is, how to deploy it effectively, and what sampling plans guarantee. This includes management, R&D, and quality personnel. In particular, production and process engineers, manufacturing and design engineers, purchasing agents and managers, and quality engineers, inspectors, supervisors, and managers.

1.3 What Are Sampling Plans?

Acceptance Sampling is based on the notion of *probability*: Although we cannot deduce from a sample about the exact quality of the entire batch, we can reach

conclusions with a given certainty level. For example, using a sampling plan and examining a sample, we might conclude that “we are 95% certain that the percent of non-conforming items in the entire batch is no more than 1%”.

Sampling plans consist of *criteria*, such as the size of the sample to inspect and *decision rules* which tell us whether to accept or reject the batch, based on the quality of the inspected sample.

Samples are typically drawn *at random*. Drawing a random sample is sometimes operationally costly or inconvenient, for instance, when a shipment consists of many boxes that are piled one on top of the other. However, random sampling is extremely important for drawing correct decisions. Although it might be easier to sample all items from the top-most box, the sample information might be biased if the top-most box is slightly different in quality from all the other boxes in the shipment.

Sampling plans are divided into two general categories, depending on the quality property that is being measured:

- **Sampling plans for attributes** are used for **pass/fail (go/no-go) classifications** such as whether a phone call disconnects, and for the **number of non-conformities**, such as the number of disconnected calls per hour.
- **Sampling plans for variables** are used for **continuous measurements** such as the length of a phone call.

Sampling plans can also range from single-stage plans, where a single sample is drawn from a batch, to double-stage plans, where one or two samples are taken, to multiple-stage plans, where one or more samples are drawn.

1.4 Terminology

The terms *lot*, *batch*, and *shipment* are used interchangeably to denote the collection of items to which an accept/reject decision must be made. The size of a batch is denoted by N .

The term *sample* refers to a subset of a batch that is typically drawn at random, and is fully inspected. Sample size is denoted by n .

6 Introduction

Producer refers to the party who manufactures or creates the good or service of interest. The producer is assumed to produce items on a regular basis.

Consumer refers to the party who purchases goods or services from the producer. The consumer receives batches of goods or services from the producer.

We use X to denote the random variable measuring the quantity of interest in the sample. For pass/fail data, X measures the number of failures in the sample. For example, if a sample of phone calls contains 3 disconnected calls, we denote this by $X=3$. For continuous measurements we use X_i to denote the measurement of the i^{th} item in the sample. For example, if the first milk carton in a sample of 10 cartons contains 500cc, we use the notation $X_1=500$.

p is used to denote the proportion of non-conforming (“failed”) items in the batch.

1.5 What determines a sampling plan?

Producer’s Side:

A producer produces items on a continuous basis (think of a production line). Let us assume that the production line quality meets a baseline requirement called *Acceptable Quality Level* (AQL). The producer would like to assure that batches from this process will be accepted with a high probability.

The *producer’s risk* (denoted α) is the chance that a batch from a process with quality AQL is rejected.

Consumer’s Side:

The consumer cares about the quality of individual batches. The consumer’s required per-batch quality is called *Lot Tolerance Percent Defective* (LTPD). The consumer would like to reject batches with quality LTPD or worse with high probability.

The *consumer’s risk* (denoted β) is the chance that a batch with quality LTPD or worse is accepted.

A sampling plan is a scheme aimed at balancing the requirements of the producer and the consumer. It does so by **balancing the consumer’s risk (α) and the producer’s risk (β)**.

We will formalize these concepts in the next sections, within the context of specific sampling plans.

1.6 Problems

- 1) What are two advantages of acceptance sampling over 100% inspection?
- 2) What is the main purpose of acceptance sampling?
- 3) “Bee Healthy” is a coop of honey collectors in India. The coop regularly inspects batches of their honey jars to assure that quality is up to the standards of an organic certifying agency. A honey jar can either be conforming or non-conforming. Each batch consists of 300 jars.
 - a) Should “Bee Healthy” use sampling plans for attributes or for variables? Explain.
 - b) Is “Bee Healthy” considered the producer or the consumer? Explain.
 - c) What is the meaning of the producer’s risk in this case?
 - d) How should a sample be drawn from each batch of 300 jars?